



Model : AS

Feature: tempered glass front door, vented split rear door.

AS Cabinet Package Contents:

- Cabinet Frame 2pcs
- Top Cover 1pc
- Glass Front door 1pc
- Cage nuts&screws 1bag
- Castor 4pcs
- Side Panel 2pcs
- Bottom Panel 1pc
- Vented split rear door 1 pair
- leveling feet 4pcs
- Keys 1set

Specification

Model No.	Capacity	Dimension	Assembled packing(CBM)	Unassembled packing(CBM)
AS6618	18U	600x600mm	0.40	0.17
AS6818		600x800mm	0.53	0.20
AS6018		600x1000mm	0.65	0.23
AS6622	22U	600x600mm	0.49	0.20
AS6822		600x800mm	0.63	0.25
AS6022		600x1000mm	0.78	0.30
AS6627	27U	600x600mm	0.57	0.23
AS6827		600x800mm	0.75	0.29
AS6027		600x1000mm	0.93	0.34
AS6632	32U	600x600mm	0.66	0.28
AS6832		600x800mm	0.87	0.33
AS6032		600x1000mm	1.10	0.38
AS6637	37U	600x600mm	0.75	0.30
AS6837		600x800mm	0.99	0.35
AS6037		600x1000mm	1.23	0.42
AS6642	42U	600x600mm	0.84	0.32
AS6842		600x800mm	1.10	0.38
AS6042		600x1000mm	1.37	0.46
AS8842		800x800mm	1.50	0.43
AS8042		800x1000mm	1.62	0.54
AS8242		800x1200mm	2.16	0.61

- Standard: Comply with ANSI/EIARS-310-D, DIN41491; PART1, IEC297-2, DIN41494; PART7, GB/T3047.2-92 standard. Compatible with metric ETSI and 19 inch international standard.
- Material: Zinc plated mounting profiles, SPCC Cold rolled steel.
- Material thickness: Mounting profile: 2.0mm, mounting rails: 1.2mm, others: 1.0mm.
- Loading Capacity: 800kg.
- Protection grade: IP20.
- Ventilation Rate of Cabinet doors: $\geq 75\%$.
- Surface Finish: Degreasing, Pickling, Phosphating, Powder coating.
- Color: RAL9004(Black), RAL7035(Grey white).




OEM service



Door frame with vented holes



19" horizontal PDU



Grounding mark



Pre-punched holes for cabling



Cooling fan unit (optional)